

**IIkW (I5HP) SPINDLE 580 x 400 mm TABLE** 510 x 400 x 450 mm TRAVEL 8,000 RPM SPINDLE (12,000 RPM OPTIONAL) **SOLID CASTING 2,400 KG** 



## XYZ 500 TMC offers maximum workshop flexibility in a compact footprint.

The XYZ 500 TMC is the smallest machine in the toolroom machining centre range. This new range combines the ease of use offered by the ProtoTRAK® RMX control with the production capability of a machine with a toolchanger. With axis travels of  $510 \times 400 \times 450$  mm and 8,000 rpm spindle, this combined with the ProtoTRAK® RMX control makes it unique in the market as it can be used manually with the X Y and Z hand wheels, or in full CNC mode utilising the 12 station carousel tool changer and its full guarding. Built on a proven machine platform using the latest linear rail technology, the

XYZ 500 TMC is the best of both worlds.



IIkW (15HP) SPINDLE 580 x 400 mm TABLE 510 x 400 x 450 mm TRAVEL 8,000 RPM SPINDLE (12,000 RPM OPTIONAL) SOLID CASTING 2,400 KG

## **Standard Equipment**

ProtoTRAK® touchscreen RMX control.

Optimised digital servo drives.

Flood coolant.

Worklight.

12 station carousel tool changer.

Easy clean swarf tray.

Steel concertina guards on all axis.

Powder coated guarding.

Pull studs.

**USB** ports.

Ethernet.

## **Optional Equipment**

4th axis rotary table.

Swarf Conveyor and bin.

12,000 rpm spindle.

Through spindle coolant.

Remote electronic hand wheel.

Movable electronic hand wheels for setting, manual operation and TRAKing®.

Side vision panels.

Offline RMX programming.

**DXF** Convertor.

Parasolid Convertor.

Programmable 4th axis.


Coolant washdown gun.


Remote stop go switch.

	XYZ 500 TMC
X travel	510 mm
Y travel	400 mm
Z travel	450 mm
Table size	580 × 400 mm
Spindle centre to column	415 mm
Spindle to table	100 - 550 mm
Column front to table centre	215 - 615 mm
Rapid feed XYZ axis	20 M/min
Cutting feed rates	1-20,000 mm/min
Max table load	250 kg
T slot size	16 mm
T slot number & pitch	3 @ 125 mm
Spindle speed	5-8,000 rpm
Spindle motor	likW (I5HP)
Spindle taper	BT 40
Tool magazine capacity	12 carousel
Tool change time tool to tool	8 sec
Max tool diameter	100 mm
Max tool weight	6 kg
Coolant capacity	105 L
Ballscrew size (grade C3)	28 mm P8
AC servo motor size	X and Y 5Nm, Z 10Nm
Machine weight	2,400 kg
Footprint W×D×H	1,660 × 1,860 × 2,300 mm

## With Linear Rail Ball Bearing Slides

New advances in Linear Rail Technology have enabled XYZ to produce a highly cost effective range of VMCs.





Part of the XYZ Milling Catalogue which includes:
ProtoTRAK® Turret Mills.
ProtoTRAK® Bed Mills.
Vertical Machining Centres.
4+1 & 5 Axis Simultaneous VMCs.
Manual Mills & Lathes.
Grinders.
Tooling & Accessories.



Visit www.xyzmachinetools.com or the YouTube channel to see the video.