

XYZ PROTURN RLX 425

SPINDLE 7.5 kW / (10 HP)
AVAILABLE AS A 1.25 AND 2 METRE GAP BED LATHE
SWING OVER BED 480 mm
SPINDLE BORE 80 mm
DISTANCE BETWEEN CENTRES 1,250 & 2,000 mm
MAX 2,500 RPM



XYZ PROTURN RLX 425 x 1.25 metre

| | XYZ RLX 425-1.25 and 2 metre |
|---------------------------|-------------------------------|
| Swing over bed | 480 mm |
| Swing in gap | 700 mm |
| Gap in front of faceplate | 170 mm |
| Swing over cross slides | 257 mm |
| Cross slide travel | 230 mm |
| Distance between centres | 1,250 / 2,000 mm |
| Maximum cutting length | 1,080 / 1,900 mm |
| Spindle bore | 80 mm |
| Spindle nose | D 1-8 camlock |
| Spindle taper | MT7 in bush |
| Spindle motor | 7.5 kW (10 HP) |
| Spindle speeds | 25-2,500 rpm (3 ranges) |
| Tailstock travel | 160 mm |
| Tailstock taper | MT 5 |
| Tailstock diameter | 75 mm |
| Bed width | 370 mm |
| Footprint L x D x H | 2,600/3,450 x 1,480 x 1,830mm |
| Weight | 2,700 / 3,700 kg |

Standard Equipment

250 mm 3 Jaw Chuck.
Constant Surface Speed.
TRAKing®.
3 Range Headstock.
Quick Change Toolpost with 6 Holders.
Rapid Traverse with Joy Stick.
Air Assist Tailstock.
Interlocked Chuck Guard and Main Guard.
Auto Lubrication.
Flood Coolant.
Worklight.
Centres and Bushes.

Optional Equipment

Advanced Features.
Verify Solid Model Graphics.
DXF File Converter.
Offline Programming.
Drilling Attachment.
Adjustable Back Stop.
Faceplates, Steadies, Chucks and Collet Chucks.
4 or 8 Station Auto Indexing Toolpost.
Swarf Conveyor.



Part of the **XYZ Turning Catalogue** which includes:
ProtoTRAK® Lathes.
Turning Centres.
XL Extra Large Lathes.
Oil Country Lathes.
Mobile Robotic Automation.
Manual Mills & Lathes.
Grinders.
Tooling & Accessories.



Visit www.xyzmachinetools.com or the YouTube channel to see the video.