

5.75 kW / (7.5 HP) PROGRAMMABLE VARIABLE SPEED HEAD 58" x 14" (1,470 x 356 mm) TABLE 40" x 23.5" x 23" (1,016 x 596 x 584 mm) TRAVEL PROGRAMMABLE 5,000 RPM SPINDLE

If your work needs more spindle power then the RMX 4000 is the machine for you, with 7.5 HP available and fully programmable spindle speed.

The **XYZ RMX 4000** has a 1,000 mm 'X' travel offering massive capacity at a very competitive price.

Standard Equipment

Programmable Variable Speed Head.

TRAKing®.

Hard Box Ways.

3 Axis DRO.

2 or 3 Axis CNC.

Precision Ground Ballscrews.

Coolant.

Air Power Drawbar.

Work Light.

Auto Lubrication.

Interlocked Guarding.

Optional Equipment

Advanced Features.

Riser Blocks.


Offline Software.

Tooling, Vices etc.

DXF Converter.

Parasolid Converter.

Programmable 4th Axis.



Part of the XYZ Milling Catalogue which includes:
ProtoTRAK® Turret Mills.
ProtoTRAK® Bed Mills.
Vertical Machining Centres.
4+1 & 5 Axis Simultaneous VMCs.
Mobile Robotic Automation.
Manual Mills & Lathes.
Grinders.
Tooling & Accessories.



	XYZ RMX 4000
Spindle drive motor	5.75 kW / (7.5 HP)
Speed range	40-5,000 rpm programmable
2 Speed ranges	40-600 / 300-5,000 rpm
Table size	1,474 × 356 mm
T slots	15.9 mm 4 off
Longitudinal travel <i>X axis</i>	1,016 mm
Cross travel Y axis	596 mm
Head vertical travel Z axis	584 mm
Spindle taper	40 ISO
Quill power feeds	.038 .076 .15 mm
Quill travel	140 mm
Quill diameter	II6 mm
Max table load	850 kg
Head tilt left to right	45°- 45°
Throat depth	610 mm
Net weight approx	3,190 kg

